

SanRex®

Thyristor/Thyristor Thyristor/Diode

$I_{T(AV)} = 200A$, $V_{RRM} = 800 - 1800V$

SanRex Thyristor/Thyristor (**SCA series**), Thyristor/Diode (**SCE series**) are designed for general purpose high voltage applications. **The modules are an Isolated Industrial Standard Package.**

Features

- * Glass-passivated Junctions Feature
- * High Surge Current ($I_{TSM}=6500A$)
- * Low On-State Voltage Drop ($V_{TM}=1.4V$)
- * UL E76102 approved
- * RoHS compliance

Typical Applications

- * Welders
- * Uninterruptible Power Supplies (UPS)
- * Temperature and Lighting Controls
- * Soft Starters
- * Battery Chargers

< Maximum Ratings >

$T_j = 25^\circ C$ (unless otherwise noted) per diode

Symbol	Item	Ratings				Unit
		SCA200AA80 SCE200AA80	SCA200AA120 SCE200AA120	SCA200AA160 SCE200AA160	SCA200AA180 SCE200AA180	
V_{RRM}	Repetitive Peak Reverse Voltage	800	1200	1600	1800	V
V_{RSM}	Non-Repetitive Peak Reverse Voltage	960	1300	1700	1900	V
V_{DRM}	Repetitive Peak Off-state Voltage	800	1200	1600	1800	V
$I_{T(AV)}$	Average On-state Current	$T_C = 82^\circ C$			200	A
$I_{T(RMS)}$	R.M.S. On-state Current	$T_C = 82^\circ C$			314	A
I_{TSM}	Surge On-state Current	1/2 cycle, 50Hz/60Hz, Peak value, Non-repetitive			6000/6500	A
$I^2 t$	$I^2 t$ (for fusing)	Value for one cycle surge current			180000	$A^2 s$
P_{GM}	Peak Gate Power Dissipation				10	W
$P_{G(AV)}$	Average Gate Power Dissipation				3	W
I_{FGM}	Peak Gate Current				3	A
V_{FGM}	Peak Gate Voltage (Forward)				10	V
V_{RGM}	Peak Gate Voltage (Reverse)				5	V
di/dt	Critical Rate of Rise of On-state Current	$I_G=100mA$, $V_D=1/2V_{DRM}$, $dig/dt=0.1A/$				