


High Current, Low Profile Inductors

Flat-Pac™ FP3 Series



Description

- Lead free and RoHS compliant
- 155°C maximum total temperature operation
- Low profile high current inductors
- Inductance range 0.1μH to 15μH
- Design utilizes high temperature powder iron alloy material with a non-organic binder to eliminate thermal aging
- 7.25x6.7x3.0mm Surface mount package
- Magnetically shielded, low EMI
- Current rating up to 34.7Adc (Higher peak currents may be attained with a greater rolloff, see rolloff curve)
- Frequency range up to 2MHz

Applications

- Voltage Regulator Modules (VRMs)
- Multi-phase regulators
- Desktop and server VRMs and EVRDs
- Notebook regulators
- Battery power systems
- Graphics cards
- Point-of-load modules

Environmental Data

- Storage temperature range (component): -40°C to +155°C
- Operating ambient temperature range: -40°C to +155°C (ambient plus self temperature rise)
- Solder reflow temperature: J-STD-020D

Packaging

- Supplied in tape-and reel packaging, 1700 parts per 13" diameter reel

Product Specifications

Part Number ⁽⁶⁾	OCL ⁽¹⁾ μH ± 15%	I _{rms} ⁽²⁾ Amps	I _{sat} ⁽³⁾ Amps 10%	I _{sat} ⁽⁴⁾ Amps 15%	DCR mOhms @ 20°C Typ.	DCR mOhms @ 20°C Max.	K-factor (5)
FP3-R10-R	0.10	19.0	27	34.7	1.00	1.21	803
FP3-R20-R	0.22	15.3	16	20.8	1.54	1.88	482
FP3-R47-R	0.44	10.9	11.6	14.9	3.05	3.67	344
FP3-R68-R	0.72	9.72	9.0	11.6	3.85	4.63	268
FP3-1R0-R	1.10	6.26	7.4	9.5	9.40	11.2	219
FP3-1R5-R	1.50	5.78	6.2	8.0	10.0	13.1	185
FP3-2R0-R	2.00	5.40	5.4	6.9	11.5	15.0	161
FP3-3R3-R	3.20	3.63	4.3	5.5	24.5	30.0	127
FP3-4R7-R	4.70	3.23	3.5	4.2	34.9	40.0	105
FP3-8R2-R	8.5	2.91	2.6	3.4	61.6	74.0	78
FP3-100-R	10.9	2.30	2.3	3.0	84.2	101	69
FP3-150-R	14.9	2.22	2.0	2.5	106.0	127	59

1) OCL (Open Circuit Inductance) Test parameters: 100kHz, 0.1V_{rms}, 0.0Adc

2) I_{rms} DC current for an approximate ΔT of 40°C without core loss. Derating is necessary for AC currents. PCB layout, trace thickness and width, air-flow, and proximity of other heat generating components will affect the temperature rise. It is recommended that the temperature of the part not exceed 155°C under worst case operating conditions verified in the end application.

3) I_{sat}¹ Amps Peak for approximately 10% rolloff @ 20°C

4) I_{sat}² Amps Peak for approximately 15% rolloff @ 20°C

5) K-factor: Used to determine B_{p-p} for core loss (see graph). B_{p-p} = K*L*ΔI B_{p-p}: (Gauss), K: (K factor from table), L: (Inductance in μH), ΔI (Peak to peak ripple current in Amps).

6) Part number definition:


FP3 = product code and size

xxx = inductance value in μH

R = decimal point (if no "R" is present, the 3rd digit equals the number of zeros)

"-R" suffix = RoHS complaint


Dimensions - mm



Part Marking:

- FP3 (Product code and size)
- xxx = (Inductance=(Inductance value in μH)
- R = decimal point (if no "R" is present, the 3rd digit equals the number of zeros)
- YWW = Date code
- L = Location code


Packaging Information - mm




Supplied in tape and reel packaging, 1700 parts on a 13" diameter reel.

Inductance Characteristics


OCL vs. Isat



Core Loss



Temperature Rise vs. Watt Loss



Solder Reflow Profile




Table 1 - Standard SnPb Solder (T_c)

Package Thickness	Volume mm^3 <350	Volume mm^3 ≥ 350
<2.5mm	235°C	220°C
$\geq 2.5\text{mm}$	220°C	220°C

Table 2 - Lead (Pb) Free Solder (T_c)

Package Thickness	Volume mm^3 <350	Volume mm^3 350 - 2000	Volume mm^3 >2000
<1.6mm	260°C	260°C	260°C
1.6 - 2.5mm	260°C	250°C	245°C
>2.5mm	250°C	245°C	245°C

Reference JDEC J-STD-020D

Profile Feature	Standard SnPb Solder	Lead (Pb) Free Solder
Preheat and Soak		
• Temperature min. (T_{smin})	100°C	150°C
• Temperature max. (T_{smax})	150°C	200°C
• Time (T_{smin} to T_{smax}) (t_s)	60-120 Seconds	60-120 Seconds
Average ramp up rate T_{smax} to T_p	3°C/ Second Max.	3°C/ Second Max.
Liquidous temperature (T_L)	183°C	217°C
Time at liquidous (t_L)	60-150 Seconds	60-150 Seconds
Peak package body temperature (T_p)*	Table 1	Table 2
Time (t_p)** within 5 °C of the specified classification temperature (T_c)	20 Seconds**	30 Seconds**
Average ramp-down rate (T_p to T_{smax})	6°C/ Second Max.	6°C/ Second Max.
Time 25°C to Peak Temperature	6 Minutes Max.	8 Minutes Max.

* Tolerance for peak profile temperature (T_p) is defined as a supplier minimum and a user maximum.

** Tolerance for time at peak profile temperature (t_p) is defined as a supplier minimum and a user maximum.

North America

Cooper Electronic Technologies
1225 Broken Sound Parkway NW
Boca Raton, FL 33487-3533
Tel: 1-561-998-4100
Fax: 1-561-241-6640
Toll Free: 1-888-414-2645

Cooper Bussmann
P.O. Box 14460
St. Louis, MO 63178-4460
Tel: 1-636-394-2877
Fax: 1-636-527-1607

Europe

Cooper Electronic Technologies
Cooper (UK) Limited
Burton-on-the-Wolds
Leicestershire • LE12 5TH UK
Tel: +44 (0) 1509 882 737
Fax: +44 (0) 1509 882 786

Cooper Electronic Technologies
Avda. Santa Eulalia, 290
08223
Terrassa, (Barcelona), Spain
Tel: +34 937 362 812
+34 937 362 813
Fax: +34 937 362 719

Asia Pacific

Cooper Electronic Technologies
1 Jalan Kilang Timor
#06-01 Pacific Tech Centre
Singapore 159303
Tel: +65 278 6151
Fax: +65 270 4160

The only controlled copy of this Data Sheet is the electronic read-only version located on the Cooper Bussmann Network Drive. All other copies of this document are by definition uncontrolled. This bulletin is intended to clearly present comprehensive product data and provide technical information that will help the end user with design applications. Cooper Bussmann reserves the right, without notice, to change design or construction of any products and to discontinue or limit distribution of any products. Cooper Bussmann also reserves the right to change or update, without notice, any technical information contained in this bulletin. Once a product has been selected, it should be tested by the user in all possible applications.

Life Support Policy: Cooper Bussmann does not authorize the use of any of its products for use in life support devices or systems without the express written approval of an officer of the Company. Life support systems are devices which support or sustain life, and whose failure to perform, when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in significant injury to the user.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Eaton:](#)

[FP3-100-R](#) [FP3-R10-R](#) [FP3-R20-R](#) [FP3-R47-R](#) [FP3-R68-R](#) [FP3-1R0-R](#) [FP3-1R5-R](#) [FP3-150-R](#) [FP3-2R0-R](#)
[FP3-4R7-R](#) [FP3-8R2-R](#)